



Part:

M465MVLV/-5/-55/-330

Product ID:

Transtar Synthetic Low Viscosity Multi-Vehicle Automatic Transmission Fluid

Description:

A low viscosity high performance synthetic multi-purpose power transmission fluid for many passenger car and light truck automatic transmissions built after 2006.

Feature	Benefit
Full synthetic	Improved oxidation resistance and cold flow
Wear protection	Long term component durability
Corrosion inhibition	Helps to protect components from corrosion and rust
Low viscosity	Allows for improved fuel economy in newer transmission designs

Suitable for use in applications where the following fluids are required:

GM: DEXRON VI	Hyundai/Kia: SP-IV, SPH-IV	ZF: Lifeguard 6&8
Ford: MERCON LV, SP	Mazda: FZ	Nissan/Infiniti: Matic-S
Honda: DW-1	Mitsubishi: ATF-J3	JASO M315 1A-LV
Toyota/Lexus/Scion: Type WS	Mercedes: MB 236.12/14/15/41	

Extended application list available

Properties	Method	Typical Values
Color	--	Red
Clarity	--	Clear
Odor	--	Mild
Viscosity at 100°C (cSt)	ASTM D445	5.8
Viscosity at 40°C (cSt)	ASTM D445	28.6
Viscosity Index	ASTM D2270	152
API Gravity	ASTM D1298	35.8
Specific gravity	ASTM D1298	0.846
Density (Lbs/Gallon)	ASTM D1299	7.05
Flash Point (°C)	ASTM D97	206
Pour Point (°C)	ASTM D92	-43
Brookfield Viscosity at -40°C (cP)	ASTM D2983	9,000

Date: 10/7/2016

Version: I

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. This information is subject to change without notice.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices. Follow local disposal requirements.

See safety data sheet (SDS) for health information.